



# TECHNICAL DATA SHEET

## /// FLEXSTOR® II - 2U

### GENERAL

Drive Type	Half-height, Full-height LTO-3 - LTO-7(8*)
Interface Type	SCSI, SAS or Fibre Channel
Media Type	Ultrium-3, -4, -5, -6, -7, (-8*) (Drive dependent)

### FORM FACTOR

19" rack mount	2 rack Unit high
----------------	------------------

### CONFIGURATION

Drive Capacity	2 half-height LTO or 1 Full-height LTO
Slot Capacity	24
Mailslot Quantity	1
Number of Magazines	2

### CAPACITY

Native Capacity	120 TBytes (LTO-7)
Compressed Capacity (2,5:1)	300 TBytes (LTO-7)

### SPEED

Transfer Rate	Drive and interface dependent
---------------	-------------------------------

### RELIABILITY

Robotic MCBF	500,000 Cycles
--------------	----------------

### ACCESS AND OPERATION

Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

# TECHNICAL DATA SHEET

## /// FLEXSTOR® II - 2U

### POWER

Power Supply Quantity	1
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	160W; (Bronze 80 Plus - Green Power Supply)

### ENVIRONMENTAL REQUIREMENTS

Noise Emissions	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)
Operating Temperature	10°C bis 35°C
Operating Humidity	20% to 80% (non-condensing)

### PHYSICAL DIMENSIONS

Width	447.5 mm (17.62 inches)
Depth	740 mm (29.13 inches)
Height	87,6 mm (3,40 inches)
Weight	12kg* (26,4lbs) *without tapes



### BDT STORAGE GMBH

Saline 29 /// 78628 Rottweil /// Germany  
Tel. +49 (0) 741 / 248 01 /// Fax +49 (0) 741 / 248  
224  
www.bdt.de /// Mail info@bdt.de

The information contained herein is subject to change without notice. BDT shall not be liable for technical or editorial errors or omissions contained herein. As of: April 2013.