



TECHNICAL DATA SHEET

/// FLEXSTOR® II - 4U

GENERAL

Drive Type	Half-height, Full-height LTO-3 - LTO-7(8*)
Interface Type	SCSI, SAS or Fibre Channel
Media Type	Ultrium-3, -4, -5, -6, -7, (8*) (Drive dependent)

FORM FACTOR

19" rack mount	4 rack Unit high
----------------	------------------

CONFIGURATION

Drive Capacity	4 half-height LTO or 2 Full-height LTO
Slot Capacity	48
Mailslot Quantity	3
Number of Magazines	4

CAPACITY

Native Capacity	240 TBytes (LTO-7)
Compressed Capacity (2,5:1)	600 TBytes (LTO-7)

SPEED

Transfer Rate	Drive and interface dependent
---------------	-------------------------------

RELIABILITY

Robotic MCBF	500,000 Cycles
--------------	----------------

ACCESS AND OPERATION

Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

TECHNICAL DATA SHEET

/// FLEXSTOR® II - 4U

POWER

Power Supply Quantity	1 or 2 (2nd is redundant)
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	300W (with one supply; Bronze 80 Plus - Green Power Supply)

ENVIRONMENTAL REQUIREMENTS

Noise Emissions	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)
Operating Temperature	10°C bis 35°C
Operating Humidity	20% to 80% (non-condensing)

PHYSICAL DIMENSIONS

Width	447.5 mm (17.62 inches)
Depth	740 mm (29.13 inches)
Height	175,2 mm (6,90)
Weight	20kg* (44lbs) *without tapes



BDT STORAGE GMBH

Saline 29 /// 78628 Rottweil /// Germany
Tel. +49 (0) 741 / 248 01 /// Fax +49 (0) 741 / 248
224
www.bdt.de /// Mail info@bdt.de

The information contained herein is subject to change without notice. BDT shall not be liable for technical or editorial errors or omissions contained herein. As of: April 2013.